LED PAR LAMP

- . Excellent lens with lighting transmission over 85%.
- High quality led chip to guarantee high lumen efficiency.
- Thermal plastic heat sink to ensure heat dispassion for long lifespan.
- Efficient led driver to achieve safe and reliable quality for two years' warranty.
- CE, Rohs, ERP approval.
- · Energy-saving, Environment friendly.





03PAR20-7W/9W Plastic housing+PC cover Wattage: 7W/9W Lumen: 500im/720im Voltage: AC220-240V 50/60Hz LED Type: 2835 SMD Beam angle: 38°/60° Lamp base: E27 CCT: 2700-6500K PF: 0.5 Size: Die63xH82mm Lifespan: 25000thrs



0.3PAR30-11W/13W Plastic housing-PC cover Wattage: 11W/13W Lumen: 900lm/1000lm Voltage: AC220-240V 50/60Hz LED Type: 2835 SMD Beam angle: 387/60' Lamp base: E27 CCT: 2700-6500K PF: 0.5 Size: Dia95xH100mm Lifespan: 25000ths



Plastic housing+PC cover Wattage: 15W17W Lumen: 1200/m1380lm Voltage: AC220-240V 50/60Hz LED Type: 2385 SMD Beam angle: 38°/60° Lamp base: E27 CCT: 2700-6500K PF: 0.5 Size: Dia122x4H25mm Lifespan: 25000hrs



IP65 LED PAR LAMP

- . Excellent lens with lighting transmission over 85%.
- . High quality led chip to guarantee high lumen efficiency.
- Thermal plastic heat sink to ensure heat dispassion for long lifespan.
- Efficient led driver to achieve safe and reliable quality for two years' warranty.
- CE, Rohs, ERP approval.
- Energy-saving, Environment friendly.





03PAR38-C-15W Aluminum and plastic housing

Wattage: 15W
Lumen: 1300lm
Voltage: AC/DC 12V
LED Type: 2835SMD
Beam angle: 120°
Lamp base: E27
CCT: 2700-6500K
PF: 20.5

Size: 122*125mm

Lifespan: 25000hrs



03PAR38-C-15W Aluminum and plastic housing

Wattage: 15W
Lumen: 1300lm
Voltage: AC/DC 12V
LED Type: 2835SMD
Beam angle: 120°
Lamp base: E27
CCT: 2700-6500K
PF:>0.5
Size: 122*125mm
Lifespan: 25000hrs



03PAR38-C-15W Aluminum and plastic housing

Aluminum and plastic Wattage: 15W Lumen: 1300lm Voltage: AC/DC 12V LED Type: 2835SMD Beam angle: 120° Lamp base: E27 CCT: 2700-6500K PF: >0.5 Size: 122*125mm Lifespan: 25000hrs

